Searching PAJ Page 1 of 2

## PATENT ABSTRACTS OF JAPAN

(11)Publication number:

07-256253

(43)Date of publication of application: 09.10.1995

(51)Int.Cl.

C02F 1/44 B01D 63/02 B01D 65/02

B01D 65/02 B01D 65/10 C02F 1/50 C02F 1/50 C02F 1/50

C02F 1/50 C02F 1/50 C02F 1/50

C02F 1/78

(21)Application number: 06-321297

(71)Applicant : OTV OMNIUM DE TRAITEMENT &

DE VALORISATION SA

(22)Date of filing:

30.11.1994

(72)Inventor: COTE PIERRE

FAIVRE MICHEL MOULIN CATHERINE DESBOS GILBERT

(30)Priority

Priority number : 93 9314570


Priority date : 30.11.1993

Priority country: FR

## (54) INSTALLATION FOR MAKING WATER POTABLE WITH SUBMERGED FILTERING MEMBRANE

## (57)Abstract:

PURPOSE: To reduce the size of a water treatment installation by providing this installation with a reactor demarcating at least one treatment chamber, a plurality of filtering membranes which are arranged in the treatment chamber and are designed to be submerged into the water to be treated and an ozone-injection means.



Searching PAJ Page 2 of 2

CONSTITUTION: The installation for treating the water for the purpose of making the water potable is provided with a wall 9 dividing the inside of the reactor 1 to an upper water treatment chamber 2 and a lower chamber 10. A plurality of filter modules 3 which are respectively housed in sheaths 5 and consist of hollow fiber bundles respectively are supported at this wall 9. The raw water is supplied by an introducing means 4 to the upper water treatment chamber 2. The recovery and destruction of the residual ozone out of the ozone injected by the ozone-injection means 6 are executed in a hood disposed above the reactor 1. The permeate past the filter modules 3 is gathered in the lower chamber 10 and is recovered by a permeate recovering means including a suction pump 17 and a permeate storage vessel 26. The permeate in the vessel 26 is reinjected into the lower chamber 10 by a back wash pump 18 at the time of the regeneration of the filter modules.